

MATERIAL SAFETY DATA SHEET

According to Regulation (EU) No 453/2010

SECTION 1 IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : VECTAIR AIROMA BABYFACE AERO-05
Product code : 1252132

1.2. Relevant identified uses of the substance or mixture and uses advised against

Application : SU22 Professional use. For industrial or institutional use. Airfreshener.

1.3. Details of the supplier of the safety data sheet

Supplier : Vectair System LTD
Unit 3, Trident Centre, Armstrong Road
RG248NU BASINGSTOKE, HAMPSHIRE, Great Britain
Telephone : +44 1256 319500
Fax : +44 1256 319520
E-mail : msds@vectairsystems.com
Website : <http://www.vectairsystems.com>

1.4. Emergency telephone number

EMERGENCY TELEPHONE NUMBER, for DOCTORS/FIRE BRIGADE/POLICE only:
GB - Telephone : +44 1256 319500 (During office hours only)
EMERGENCY TELEPHONE NUMBER (for DOCTORS only):
(24/7)

SECTION 2 HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (99/45/EC) : Extremely flammable.
CLP classification (1272/2008/EC) : Aerosols, category 1. Eye irritation, category 2. Specific target organ toxicity after single exposure, category 3.
Human health hazards : Causes serious eye irritation. May cause drowsiness or dizziness. May produce an allergic reaction. Exposure to high vapour concentrations may result in a narcotic effect. Use only as directed. Intentional misuse by deliberately concentrating and inhaling contents can be harmful or fatal.
Physical/chemical hazards : Extremely flammable. Keep away from sources of ignition — No smoking. Do not spray on a naked flame or any incandescent material. Do not spray near fire, sources of heat or live electrical equipment. Aerosol may explode from internal pressure build-up when exposed to temperatures exceeding 50 °C.
Environmental hazards : Not classified as dangerous according to statutory EC-Directives.
Other information : Keep out of the reach of children. Caution: Do not breathe spray. Use only in well-ventilated areas. Spray in short intervals for a short period only. Ventilate well after use. Harmful to house pets.

2.2. Label elements

Label elements (99/45/EC):
Hazard symbols :



F+: Extremely flammable

R- and S-phrases : R12 Extremely flammable.

MATERIAL SAFETY DATA SHEET

According to Regulation (EU) No 453/2010

S2 Keep out of the reach of children.
S16 Keep away from sources of ignition — No smoking.
S23 Aerosol Do not breathe spray.
S51 Use only in well-ventilated areas.

Additional labelling : Important: Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C.
Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Label elements (1272/2008/EC):

Hazard pictograms :



Signal word : Danger

H- and P-phrases : H222 Extremely flammable aerosol.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H229 Pressurised container: May burst if heated.
EUH208 Contains ... May produce an allergic reaction. Reference is made to additional labelling for full text of EUH208*.
P251 Do not pierce or burn, even after use.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P261 spray Avoid breathing spray.
P403 Store in a well-ventilated place.

Additional labelling (99/45/EC and/or 1272/2008/EC)

: * Contains Coumarin 3-Methyl-4-(2,6,6-trimethyl-2-cyclohexen-1-yl)-3-buten-2-one d-Limonene Citronellol Geraniol Benzyl salicylate May produce an allergic reaction.
: Where the mixture is labelled in accordance with Regulation (EC) No 1272/2008 (CLP) the packaging shall (also) carry the text: Contains: Propan-2-ol

2.3. Other hazards

Other information : The classification of this product is based on the non-aerosolised form of the mixture (on basis of section 1.1.3.7. of Regulation (EC) No 1272/2008). Does not contain PBT or vPvB substances in concentrations higher than 0,1%.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.2. Mixtures

Product description : Mixture.

Information on hazardous substances:

| Substance name | Concentration (w/w) (%) | CAS nr. | EC number | Symbols | R-phrases |
|-----------------|-------------------------|----------|-----------|---------|-------------|
| Isobutane | 50 - 75 | 75-28-5 | 200-857-2 | F+ | 12 |
| Ethanol | 10 - < 20 | 64-17-5 | 200-578-6 | F | 11 |
| Propane | 10 - < 20 | 74-98-6 | 200-827-9 | F+ | 12 |
| Propan-2-ol | 5 - < 10 | 67-63-0 | 200-661-7 | F; Xi | 11-36-67 |
| Propyleneglycol | 1 - < 5 | 57-55-6 | 200-338-0 | ---- | ---- |
| Butane | 1 - < 5 | 106-97-8 | 203-448-7 | F+ | 12 |
| Coumarin | 0,1 - < 1 | 91-64-5 | 202-086-7 | Xn | 22-43-48/22 |

MATERIAL SAFETY DATA SHEET

According to Regulation (EU) No 453/2010

| | | | | | |
|--|-----------|-----------|-----------|-------|-------------------|
| 3-Methyl-4-(2,6,6-trimethyl-2-cyclohexen-1-yl)-3-buten-2-one | 0,1 - < 1 | 127-51-5 | 204-846-3 | Xi; N | 43-51/53 |
| d-Limonene | < 0,1 | 5989-27-5 | 227-813-5 | Xi; N | 10-38-43-50/53-65 |
| Citronellol | < 0,1 | 106-22-9 | 203-375-0 | Xi; N | 38-43-51/53 |
| Geraniol | < 0,1 | 106-24-1 | 203-377-1 | Xi | 38-41-43 |
| Benzyl salicylate | < 0,1 | 118-58-1 | 204-262-9 | Xi; N | 43-51/53 |
| Pentyl salicylate | < 0,1 | 2050-08-0 | 218-080-2 | N | 51/53 |

Reference is made to chapter 16 for full text of each relevant R phrase. Occupational exposure limit(s), if relevant, are listed in section 8.

| Substance name | REACH nr. | Hazard Class | Pictograms | H-phrases |
|--|------------------|---|----------------------------|------------------------------|
| Isobutane | 01-2119485395-27 | Flam. Gas 1; Press. Gas | GHS02; GHS04 | H220; H280 |
| Ethanol | 01-2119457610-43 | Flam. Liq. 2; Eye Irrit. 2 | GHS02; GHS07 | H225; H319 |
| Propane | 01-2119486944-21 | Flam. Gas 1; Press. Gas | GHS02; GHS04 | H220; H280 |
| Propan-2-ol | 01-2119457558-25 | Flam. Liq. 2; Eye Irrit. 2; STOT SE 3 | GHS02; GHS07 | H225; H319; H336 |
| Propyleneglycol | 01-2119456809-23 | ---- | ---- | ---- |
| Butane | 01-2119474691-32 | Flam. Gas 1; Press. Gas | GHS02; GHS04 | H220; H280 |
| Coumarin | 01-2119949300-45 | Acute Tox. 4; Skin Sens. 1B; STOT RE 2 | GHS07; GHS08 | H302; H317; H373 |
| 3-Methyl-4-(2,6,6-trimethyl-2-cyclohexen-1-yl)-3-buten-2-one | | Skin Sens. 1; Aquatic Chronic 2 | GHS07; GHS09 | H317; H411 |
| d-Limonene | 01-2119529223-47 | Flam. Liq. 3; Skin Irrit. 2; Skin Sens. 1B; Asp. Tox. 1; Aquatic Acute 1; Aquatic Chronic 1 | GHS02; GHS07; GHS09; GHS08 | H226; H304; H315; H317; H410 |
| Citronellol | 01-2119453995-23 | Eye Irrit. 2; Skin Irrit. 2; Skin Sens. 1B | GHS07 | H319; H317; H315 |
| Geraniol | 01-2119552430-49 | Skin Sens. 1; Eye Dam. 1; Skin Irrit. 2 | GHS05; GHS07 | H317; H318; H315 |
| Benzyl salicylate | 01-2119969442-31 | Skin Sens. 1; Aquatic Chronic 2 | GHS07; GHS09 | H317; H411 |
| Pentyl salicylate | | Aquatic Chronic 2 | GHS09 | H411 |

Reference is made to chapter 16 for full text of each relevant H phrase.

SECTION 4 FIRST-AID MEASURES

4.1. Description of first aid measures

First aid measures

- Inhalation : Move victim into fresh air. Consult a doctor if victim feels unwell.
- Skin contact : Take off contaminated clothing. Wash off skin with plenty of water and soap before product dries up. Consult a doctor if irritation occurs.
- Eye contact : Wash out with (lukewarm) water for at least 15 minutes. Remove contact lenses. Consult a doctor.
- Ingestion : Aerosol/mist: Ingestion is unlikely to occur.

4.2. Most important symptoms and effects, both acute and delayed

Effects and symptoms

- Inhalation : May cause headache, dizziness and a feeling of sickness. May cause irritation to respiratory airways and coughing.
- Skin contact : May produce an allergic reaction. May cause dry skin and redness.
- Eye contact : Irritant. May cause redness and pain.
- Ingestion : Aerosol/mist: Ingestion is unlikely to occur.

4.3. Indication of any immediate medical attention and special treatment needed

- Note to physicians : None known.

MATERIAL SAFETY DATA SHEET

According to Regulation (EU) No 453/2010

SECTION 5 FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

- Suitable : Carbondioxide (CO₂). Alcohol resistant foam. Dry chemical. Water fog.
Not suitable : Water jet.

5.2. Special hazards arising from the substance or mixture

- Special exposure hazards : Aerosol may explode from internal pressure build-up when exposed to temperatures exceeding 50 °C. Do not expose emergency personnel to overheated aerosol containers. Water may be used to cool container and prevent explosion of the aerosol.
Hazardous thermal decomposition products : Carbon monoxide may be evolved if incomplete combustion occurs.

5.3. Advice for firefighters

- Special protective equipment for fire-fighters : Fight a fire where aerosols are involved from a protected position. Use adequate respiratory equipment in case of insufficient ventilation.

SECTION 6 ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

- Personal precautions : Danger of slipping. Clean up spills immediately. Wear shoes with non-slip soles. Avoid contact with spilled or released material. Do not breathe vapours and/or spray. Keep away from sources of ignition — No smoking. Build up of highly flammable gasses involves an explosion risk. Vapours are heavier than air. Build up (of gasses) in low areas involves risk of suffocation.

6.2. Environmental precautions

- Environmental precautions : Avoid release of product into sewers, surface water and/or ground water.
Other information : Notify authorities if any exposure to the general public or the environment occurs or is likely to occur.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Collect spilled material in containers. Collect cans in an approved container. Do not pierce aerosols. Wash away remainder with plenty of water and soap.

6.4. Reference to other sections

- Reference to other sections : See also section 8.

SECTION 7 HANDLING AND STORAGE

7.1. Precautions for safe handling

- Handling : Handle in accordance with good occupational hygiene and safety practices in well-ventilated areas. Important: Pressurized container; protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Keep away from sources of ignition — No smoking. Do not spray on a naked flame or any incandescent material. Do not spray near fire, sources of heat or live electrical equipment. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Do not breathe spray. Do not breathe vapour. Avoid contact with skin and eyes.

7.2. Conditions for safe storage, including any incompatibilities

- Storage : Keep frost-free, in a cool (< 35°), dry and well-ventilated place. Protect from sunlight and keep away from heat.

MATERIAL SAFETY DATA SHEET

According to Regulation (EU) No 453/2010

Recommended packaging : Not applicable.

7.3. Specific end use(s)

Use : Use only as directed.

SECTION 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

Occupational exposure limits : Occupational exposure limits have not been established for this product. Derived no-effect levels (DNEL) have not been established for this product. Predicted no-effect concentrations (PNEC) have not been established for this product.

Workplace exposure limits (mg/m³):

| Chemical name | Country | TWA 8 hour (mg/m ³) | STEL 15 min (mg/m ³) | Comments |
|-----------------|---------|---------------------------------|----------------------------------|---------------------------------------|
| Isobutane | | 1900 | 2400 | |
| Ethanol | GB | 1920 | - | - |
| Ethanol | | 260 | 1900 | Mac: NL |
| Propane | | 1800 | - | |
| Propan-2-ol | GB | 999 | 1250 | - |
| Propyleneglycol | GB | 474 | - | Total Vapour and Particulates |
| Propyleneglycol | | 474 | - | MAC UK: Total Vapour and Particulates |
| Butane | GB | 1450 | 1810 | - |
| Butane | | 1450 | 1810 | - |

Derived no-effect level (DNEL) for workers:

| Chemical name | Route of exposure | DNEL, short-term | | DNEL, long-term | |
|-----------------|-------------------|------------------------|-----------------|----------------------|-------------------------|
| | | Local effect | Systemic effect | Local effect | Systemic effect |
| Ethanol | Dermal | | | | 343 mg/kg bw/day |
| | Inhalation | 1900 mg/m ³ | | | 950 mg/m ³ |
| Propan-2-ol | Dermal | | | | 888 mg/kg bw/day |
| | Inhalation | | | 10 mg/m ³ | 500 mg/m ³ |
| Propyleneglycol | Inhalation | | | | 168 mg/m ³ |
| Coumarin | Dermal | | | | 0,79 mg/kg bw/day |
| | Inhalation | | | | 5,52 mg/m ³ |
| d-Limonene | Inhalation | | | | 33,3 mg/m ³ |
| Citronello | Dermal | | | | 45,8 mg/kg bw/day |
| | Inhalation | | | | 161,6 mg/m ³ |
| Geraniol | Dermal | | | | 12,5 mg/kg bw/day |
| | Inhalation | | | | 161,6 mg/m ³ |

Derived no-effect level (DNEL) for consumers:

| Chemical name | Route of exposure | DNEL, short-term | | DNEL, long-term | |
|-----------------|-------------------|-----------------------|-----------------|----------------------|------------------------|
| | | Local effect | Systemic effect | Local effect | Systemic effect |
| Ethanol | Dermal | | | | 206 mg/kg bw/day |
| | Inhalation | 950 mg/m ³ | | | 114 mg/m ³ |
| | Oral | | | | 87 mg/kg bw/day |
| Propan-2-ol | Dermal | | | | 319 mg/kg bw/day |
| | Inhalation | | | 10 mg/m ³ | 89 mg/m ³ |
| | Oral | | | | 26 mg/kg bw/day |
| Propyleneglycol | Inhalation | | | | 50 mg/m ³ |
| Coumarin | Dermal | | | | 0,39 mg/kg bw/day |
| | Inhalation | | | | 1,38 mg/m ³ |
| | Oral | | | | 0,39 mg/kg bw/day |

MATERIAL SAFETY DATA SHEET

According to Regulation (EU) No 453/2010

| | | | | |
|-------------|------------|--|--|------------------------|
| d-Limonene | Inhalation | | | 8,33 mg/m ³ |
| | Oral | | | 4,76 mg/kg bw/day |
| Citronellol | Dermal | | | 27,5 mg/kg bw/day |
| | Inhalation | | | 47,8 mg/m ³ |
| | Oral | | | 13,75 mg/kg bw/day |
| Geraniol | Dermal | | | 7,5 mg/kg bw/day |
| | Inhalation | | | 47,8 mg/m ³ |
| | Oral | | | 13,75 mg/kg bw/day |

Predicted no-effect concentration (PNEC):

| Chemical name | Route of exposure | Fresh water | Marine water | |
|-----------------|--------------------|--------------|---------------|-----------------|
| Ethanol | Water | 0,96 mg/l | 0,79 mg/l | |
| | Sediment | 3,6 mg/kg | 2,9 mg/kg | |
| | Intermittent water | | | 2,75 mg/l |
| | STP | | | 580 mg/l |
| | Soil | | | 0,63 mg/kg |
| Propan-2-ol | Oral | | | 0,72 mg/kg food |
| | Water | 140,9 mg/l | 140,9 mg/l | |
| | Sediment | 552 mg/kg | 552 mg/kg | |
| | Intermittent water | | | 140,9 mg/l |
| | STP | | | 2251 mg/l |
| Propyleneglycol | Soil | | | 28 mg/kg |
| | Oral | | | 160 mg/kg food |
| | Water | 260 mg/l | 26 mg/l | |
| | Sediment | 572 mg/kg | 57,2 mg/kg | |
| | Intermittent water | | | 183 mg/l |
| Coumarin | STP | | | 20000 mg/l |
| | Soil | | | 50 mg/kg |
| | Oral | | | 1133 mg/kg food |
| | Water | 0,019 mg/l | 0,0019 mg/l | |
| | Sediment | 0,15 mg/kg | 0,015 mg/kg | |
| d-Limonene | Intermittent water | | | 0,014 mg/l |
| | STP | | | 6,4 mg/l |
| | Soil | | | 0,018 mg/kg |
| | Oral | | | 30,7 mg/kg food |
| | Water | 0,0054 mg/l | 0,0005 mg/l | |
| Citronellol | Sediment | 1,32 mg/kg | 0,13 mg/kg | |
| | STP | | | 1,8 mg/l |
| | Soil | | | 0,262 mg/kg |
| | Oral | | | 3,33 mg/kg food |
| | Water | 0,0024 mg/l | 0,00024 mg/l | |
| Geraniol | Sediment | 0,0256 mg/kg | 0,00256 mg/kg | |
| | Intermittent water | | | 0,024 mg/l |
| | STP | | | 580 mg/l |
| | Soil | | | 0,00371 mg/kg |
| | Water | 0,0108 mg/l | 0,0010 mg/l | |
| | Sediment | 0,115 mg/kg | 0,0115 mg/kg | |
| | Intermittent water | | | 0,108 mg/l |
| | STP | | | 0,7 mg/l |
| | Soil | | | 0,0167 mg/kg |

8.2. Exposure controls

Engineering measures : Use only in well-ventilated areas. Comply with standard precautionary measures for working with chemicals.
 Hygienic measures : When using do not eat, drink or smoke.

Personal protective equipment:

The efficiency of personal protective equipment depends among other things on temperature and degree of ventilation. Always get professional advice for the particular local situation.

MATERIAL SAFETY DATA SHEET

According to Regulation (EU) No 453/2010

- Body protection : Use of specific protective industrial clothing is not required under normal conditions of use. In case of large scale exposure wear suitable protective clothing, overalls or suit, and similar boots. Suitable material: butyl. Indication of permeation breakthrough time: not known.
- Respiratory protection : Take care of sufficient ventilation. Wear suitable respiratory protection in case of large scale exposure. Suitable: gas filter type A (brown), class I or higher on e.g. a facemask in accordance with EN 140.
- Hand protection : Under normal conditions of use specific gloves are not required. Wear appropriate gloves in case of frequent or prolonged use and in case of large scale exposure. Suitable material: butyl. $\pm 0,5$ mm. Indication of permeation breakthrough time: not known.
- Eye protection : Wear appropriate safety glasses with side shields, in accordance with EN 166, when there is danger of possible eye contact.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

- Appearance : Aerosol.
- Colour : Colourless.
- Odour : Perfumed.
- Odour threshold : Not known.
- pH : Not applicable. Almost waterfree product.
- Solubility in water : Soluble.
- Partition coefficient (n-octanol/water) : Not known.
- Flash point : Not applicable. Not measurable.
- Flammability (solid, gas) : Extremely flammable.
- Auto ignition temperature : Not applicable. Aerosol container explodes before reaching the auto-ignition point.
- Boiling point/boiling range : Not known. Not measurable.
- Melting point/melting range : < 0 °C
- Explosive properties : Pressurised container: May burst if heated.
- Explosion limits (in air) : Not known. Lower explosion limit in air (%): 1,3 (Butane)
Upper explosion limit in air (%): 19 Ethanol
- Oxidising properties : Not applicable. Does not contain oxidizing substances.
- Decomposition temperature : Not applicable.
- Viscosity (20°C) : Not known.
- Viscosity (40°C) : Not known.
- Vapour pressure (20°C) : 360000 Pa
- Vapour density (20°C) : > 1 (air = 1)
- Relative density (20°C) : 0,623 g/ml
- Evaporation rate : Not known. (n-butyl acetate = 1)

SECTION 10 STABILITY AND REACTIVITY

10.1. Reactivity

- Reactivity : See sub-sections below.

10.2. Chemical stability

- Stability : Stable under normal conditions.

10.3. Possibility of hazardous reactions

- Reactivity : No other hazardous reactions known.

10.4. Conditions to avoid

- Conditions to avoid : Keep away from sources of ignition and sources of heat. See section 7.

MATERIAL SAFETY DATA SHEET

According to Regulation (EU) No 453/2010

10.5. Incompatible materials

Materials to avoid : Not applicable.

10.6. Hazardous decomposition products

Hazardous decomposition products : Not known.

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. Information on toxicological effects

No toxicological research has been carried out on this product.

Inhalation

- Acute toxicity : Calculated LC50: > 10 mg/l. Ingredients of unknown toxicity: 2 %. ATE: > 5 mg/l. Low toxicity. Not classified - based on available data, the classification criteria are not met. May cause headache, dizziness and a feeling of sickness. May cause damage to organs. Target organ(s): Central nervous system. Effect(s): Breathing of high vapour concentrations may cause central nervous system (CNS) depression resulting in dizziness, lightheadedness, headache, nausea and loss of coordination. Continued inhalation may result in unconsciousness and death.
- Corrosion/irritation : May cause irritation to respiratory airways and coughing. Not classified - based on available data, the classification criteria are not met.
- Sensitisation : Not classified - based on available data, the classification criteria are not met.
- Carcinogenicity : Not classified - based on available data, the classification criteria are not met.
- Mutagenicity : Does not contain mutagenic substances. Not classified - based on available data, the classification criteria are not met.

Skin contact

- Acute toxicity : Calculated LD50: > 5000 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw. Low toxicity. Not classified - based on available data, the classification criteria are not met.
- Corrosion/irritation : Slight irritation possible. Not classified - based on available data, the classification criteria are not met.
- Sensitisation : May produce an allergic reaction.
- Mutagenicity : Does not contain mutagenic substances. Not classified - based on available data, the classification criteria are not met.

Eye contact

- Corrosion/irritation : Irritant.

Ingestion

- Acute toxicity : Aerosol/mist: Ingestion is unlikely to occur. Calculated LD50: > 880 mg/kg.bw. Ingredients of unknown toxicity: < 1 %. ATE: > 2000 mg/kg.bw. Low toxicity. Not classified - based on available data, the classification criteria are not met. May cause hampered eyesight.
- Corrosion/irritation : Aerosol/mist: Ingestion is unlikely to occur. May cause a feeling of sickness, vomiting and diarrhoea. Not classified - based on available data, the classification criteria are not met.
- Carcinogenicity : Aerosol/mist: Ingestion is unlikely to occur. Not classified - based on available data, the classification criteria are not met.
- Mutagenicity : Aerosol/mist: Ingestion is unlikely to occur. Does not contain mutagenic substances. Not classified - based on available data, the classification criteria are not met.

Toxicological information:

| Chemical name | Property | | Method | Test animal |
|---------------|---------------------------|-------------------------|----------|-------------|
| Ethanol | Skin irritation | Non-irritant | ---- | Rabbit |
| | LD50 (dermal) | 15800 mg/kg bw | ---- | Rabbit |
| | NOAEL (inhalation) | 23000 mg/m ³ | | Rat |
| | NOAEL (oral) | 2400 mg/kg bw/d | | Rat |
| | NOAEL (fertility, oral) | 20000 mg/kg bw/d | OECD 415 | Rat |
| | Skin sensitisation | Not sensitizing | OECD 406 | Guinea pig |
| | NOAEL (development, oral) | 6400 mg/kg bw/d | | |

MATERIAL SAFETY DATA SHEET

According to Regulation (EU) No 453/2010

| | | | | |
|--|-----------------------------------|--------------------|-------------|------------------------|
| Propan-2-ol | LD50 (oral) | 10470 mg/kg bw | OECD 401 | Rat |
| | LC50 (inhalation) | > 99999 mg/m3 | OECD 403 | Rat |
| | Eye irritation | Irritant | OECD 405 | Rabbit |
| | NOEL (carcinogenicity, oral) | > 4400 mg/kg bw/d | | Mouse |
| | Genotoxicity - in vivo | Not genotoxic | OECD 478 | Mouse |
| | NOEL (carcinogenicity, inh.) | 13 mg/m3 | | |
| | Genotoxicity - in vitro | Not genotoxic | OECD 476 | |
| | Mutagenicity | Negative | OECD 471 | Salmonella typhimurium |
| | NOAEL (oral) | 870 mg/kg bw/d | ----- | Rat |
| | LD50 (oral) | 4396 mg/kg bw | ----- | Rat |
| | LD50 (dermal) | 12800 mg/kg bw | ----- | Rat |
| | LC50 (inhalation) | 46600 mg/m3 | ----- | Rat |
| | Skin irritation | Slightly irritant | OECD 404 | Rabbit |
| | Eye irritation | Irritant | OECD 405 | Rabbit |
| | NOAEL (fertility, oral) | 407 mg/kg bw/d | | Rat |
| | NOAEL (development, oral) | 400 mg/kg bw/d | | Rat |
| | NOEL (carcinogenicity, oral) | Not carcinogenic | OECD 416 | Rat |
| | Skin sensitisation | Not sensitizing | OECD 406 | Guinea pig |
| | Mutagenicity | Negative | OECD 471 | |
| | Coumarin | NOAEL (inhalation) | 12500 mg/m3 | OECD 451 |
| Genotoxicity - in vivo | | Not genotoxic | OECD 474 | Mouse |
| NOEL (carcinogenicity, inh.) | | 12500 mg/m3 | | Mouse |
| Genotoxicity - in vitro | | Not genotoxic | OECD 476 | |
| NOEL (carcinogenicity) - estimate | | Not carcinogenic | | |
| Genotoxicity - in vivo | | > 105 mg/kg bw/d | OECD 474 | Mouse |
| Mutagenicity | | Negative | OECD 471 | Salmonella typhimurium |
| Genotoxicity - in vitro | | Not genotoxic | OECD 476 | |
| Skin irritation | | Non-irritant | | Rabbit |
| NOAEL (oral) | | > 138,3 mg/kg bw/d | | Mouse |
| LD50 (oral) | | 680 mg/kg bw | ----- | Rat |
| Eye irritation | | Non-irritant | | Rabbit |
| 3-Methyl-4-(2,6,6-trimethyl-2-cyclohexen-1-yl)-3-buten-2-one | NOAEL (development, oral) | > 115 mg/kg bw/d | | Mouse |
| | Skin sensitisation | > 12500 ug/cm2 | OECD 429 | Mouse |
| | Genotoxicity - in vitro | Not genotoxic | ----- | ----- |
| | Skin sensitisation | 5450 ug/cm2 | OECD 429 | Mouse |
| | LD50 (oral) | > 5000 mg/kg bw | ----- | Rat |
| | LD50 (dermal) | > 5000 mg/kg bw | ----- | ----- |
| | NOAEL (oral) | > 3,55 mg/kg bw/d | ----- | Rat |
| | NOAEL (fertility, oral) | > 3,55 mg/kg bw/d | ----- | Rat |
| | NOAEL (development, oral) | 30 mg/kg bw/d | ----- | ----- |
| | NOEL (carcinogenicity) - estimate | Not carcinogenic | ----- | ----- |
| d-Limonene | NOEL (carcinogenicity, oral) | > 75 mg/kg bw/d | OECD 451 | Rat |
| | LC50 (inhalation) - estimate | > 5000 mg/m3 | ----- | ----- |
| | Genotoxicity - in vivo | > 2000 mg/kg bw/d | | Rat |
| | Eye irritation | Non-irritant | OECD 405 | Rabbit |
| | Mutagenicity | Negative | OECD 471 | |
| | | | | |

MATERIAL SAFETY DATA SHEET

According to Regulation (EU) No 453/2010

| | | | | | |
|--|--|-------------------------|-----------------|------------------------|------------------------|
| Citronellol | Skin sensitisation | 10075 ug/cm2 | OECD 429 | Mouse | |
| | NOAEL (development, oral) | 600 mg/kg bw/d | | Rat | |
| | Skin irritation | Irritant | ----- | ----- | |
| | NOAEL (oral) | 30 mg/kg bw/d | | Rat | |
| | NOEL (oral) | 5 mg/kg bw/d | ----- | Rat | |
| | LD50 (dermal) | > 2000 mg/kg bw | ----- | Rabbit | |
| | LD50 (oral) | 4400 mg/kg bw | ----- | Rat | |
| | Genotoxicity - in vitro | Not genotoxic | | | |
| | Eye irritation | Moderately irritant | | Rabbit | |
| | Skin irritation | Moderately irritant | Patch test | Human | |
| | NOAEL (developmental toxicity, dermal) | > 300 mg/kg bw/d | OECD 421 | Rat | |
| | NOAEL (fertility, dermal) | 300 mg/kg bw/d | OECD 421 | Rat | |
| | LD50 (dermal) | 2650 mg/kg bw | | Rabbit | |
| | LD50 (oral) | 3450 mg/kg bw | ----- | Rat | |
| | Skin irritation | Moderately irritant | | Rabbit | |
| | Geraniol | NOAEL (oral) | > 50 mg/kg bw/d | | Rat |
| Mutagenicity | | Not mutagenic | OECD 471 | Salmonella typhimurium | |
| Skin sensitisation | | 10875 ug/cm2 | OECD 429 | Mouse | |
| Genotoxicity - in vitro | | Not genotoxic | | | |
| NOAEL (developmental toxicity, dermal) | | > 300 mg/kg bw/d | OECD 421 | Rat | |
| NOAEL (fertility, dermal) | | > 300 mg/kg bw/d | OECD 421 | Rat | |
| LD50 (oral) | | 2100 mg/kg bw | ----- | Rat | |
| LD50 (dermal) | | > 5000 mg/kg bw | ----- | Rabbit | |
| NOAEL (oral) | | 1000 mg/kg bw/d | ----- | Rat | |
| Skin irritation | | Irritant | ----- | Rabbit | |
| Eye irritation | | Irritant | OECD 405 | Rabbit | |
| Genotoxicity - in vivo | | Not genotoxic | | Mouse | |
| NOEL (oral) | | > 550 mg/kg bw/d | ----- | Rat | |
| Skin sensitisation | | 3525 ug/cm2 | OECD 429 | Mouse | |
| Benzyl salicylate | | Mutagenicity | Negative | OECD 471 | Salmonella typhimurium |
| | | Genotoxicity - in vitro | Not genotoxic | OECD 476 | |
| | Mutagenicity | Negative | OECD 471 | | |
| | Eye irritation | Moderately irritant | ----- | Rabbit | |
| | Skin irritation | Non-irritant | ----- | Rabbit | |
| | Skin sensitisation | 725 ug/cm2 | OECD 429 | Mouse | |
| | LD50 (oral) | 2227 mg/kg bw | ----- | Rat | |

SECTION 12 ECOLOGICAL INFORMATION

12.1. Toxicity

No ecotoxicological research has been carried out on this product.

Ecotoxicity : Calculated LC50 (fish): 384 mg/l. Calculated EC50 (waterflea): 290 mg/l. Contains < 1 % of components with unknown hazards to the aquatic environment. Not classified - based on available data, the classification criteria are not met.

12.2. Persistence and degradability

Persistence – degradability : No specific information known.

12.3. Bioaccumulative potential

Bioaccumulative potential : No specific information known.

12.4. Mobility in soil

MATERIAL SAFETY DATA SHEET

According to Regulation (EU) No 453/2010

Mobility : Not applicable.

12.5. Results of PBT and vPvB ass

PBT/vPvB assessment : Does not contain PBT or vPvB substances in concentrations higher than 0,1%.

12.6. Other adverse effects

Other information : Not applicable.

SECTION 13 DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Product residues : Recyclable metal container. Do not puncture or burn even after use. Do not dispose empty pack with waste produced by households. Containers may be recycled. Treat product residues and non-empty pack as hazardous waste.

Additional warning : Residues may cause an explosion hazard. Do not puncture, cut or weld uncleaned drums.

European waste catalogue : Dispose hazardous waste in accordance with Directive 91/689/EEC under acknowledgement of a waste code according to Commission Decision 2000/532/EC to an official chemical waste depot.

Local legislation : Disposal should be in accordance with applicable regional, national, and local laws and regulations. Local regulations may be more stringent than regional or national requirements and must be complied with.

SECTION 14 TRANSPORT INFORMATION

14.1. UN number

UN nr. : UN 1950

14.2. UN proper shipping name

Transport name : AEROSOLS

14.3/14.4/14.5. Transport hazard class(es)/Packing group/Environmental hazards

ADR/RID/ADN (road/railway/inland waterways)

Class : 2
Classification code : 5F
Packaging group : -
Danger label : 2,1



Other information : Not intended for carriage by inland waterways in tank-vessels.

IMDG (sea)

Class : 2
Packaging group : -
EmS (fire / spill) : F - D / S - U
Marine pollutant : No

IATA (air)

Class : 2

14.6. Special precautions for user

MATERIAL SAFETY DATA SHEET

According to Regulation (EU) No 453/2010

Other information : Country specific variations may apply. It is possible that a "Limited Quantity" exemption applies to the transport of this product.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Marpol : Not intended to be carried in bulk according to International Maritime Organisation (IMO) instruments. Packaged liquids are not considered bulk.

SECTION 15 REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Community regulations : Regulation (EC) No 453/2010 (REACH), Regulation (EC) No 1272/2008 (CLP), 75/324/EEC (aerosols) and other regulations.
: In the UK it is recommended that all aerosols should be labelled on the back with the warning about the dangers of volatile solvent abuse. The label should contain the badge 'Solvent Abuse Can Kill Instantly' accompanied by the phrase 'Use only as directed'.

15.2. Chemical safety assessment

Chemical safety assessment : Not applicable.

SECTION 16 OTHER INFORMATION

16.1. Other information

The information in this safety data sheet is compiled in compliance with Regulation (EC) No 453/2010 dated 20 May 2010 and accurate to the best of our knowledge and experience at the date of issue specified. It is the user's obligation to use this product safely and to comply with all applicable laws and regulations concerning the use of the product. This safety data sheet complements the technical information sheets but does not replace them and offers no warranty with regard to product properties.

Users are also forewarned for any hazards involved when the product is used for other purposes than those for which it is designed.

Changed or new information with regard to the previous release is indicated with an asterisk (*).

Full text of R-phrases mentioned in section 3:

| | |
|--------|--|
| R10 | Flammable. |
| R11 | Highly flammable. |
| R12 | Extremely flammable. |
| R22 | Harmful if swallowed. |
| R36 | Irritating to eyes. |
| R38 | Irritating to skin. |
| R41 | Risk of serious damage to eyes. |
| R43 | May cause sensitisation by skin contact. |
| R48/22 | Harmful: danger of serious damage to health by prolonged exposure if swallowed. |
| R50/53 | Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R51/53 | Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
| R67 | Vapours may cause drowsiness and dizziness. |

Full text of H-phrases mentioned in section 3:

| | |
|------|---|
| H220 | Extremely flammable gas. |
| H225 | Highly flammable liquid and vapour. |
| H226 | Flammable liquid and vapour. |
| H280 | Contains gas under pressure; may explode if heated. |
| H302 | Harmful if swallowed. |
| H315 | Causes skin irritation. |
| H317 | May cause an allergic skin reaction. |
| H318 | Causes serious eye damage. |
| H319 | Causes serious eye irritation. |

MATERIAL SAFETY DATA SHEET

According to Regulation (EU) No 453/2010

| | |
|------|--|
| H336 | May cause drowsiness or dizziness. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |
| H410 | Very toxic to aquatic life with long lasting effects. |
| H411 | Toxic to aquatic life with long lasting effects. |

Full text of hazard classes mentioned in section 3:

| | |
|-------------------|---|
| Flam. Gas 1 | : Flammable gas, category 1. |
| Press. Gas | : Compressed gas. |
| Flam. Liq. 2 | : Flammable liquid, category 2. |
| Flam. Liq. 3 | : Flammable liquid, hazard category 3. |
| Acute Tox. 4 | : Acute toxicity, category 4. |
| Skin Irrit. 2 | : Skin irritation, category 2. |
| Eye Dam. 1 | : Serious eye damage, category 1. |
| Eye Irrit. 2 | : Eye irritation, category 2. |
| Skin Sens. 1 | : Skin sensitization, category 1. |
| STOT SE 3 | : Specific target organ toxicity after single exposure, category 3. |
| STOT RE 2 | : Specific target organ toxicity — repeated exposure, category 2. |
| Aquatic Chronic 1 | : Hazardous to the aquatic environment — Chronic category 1. |
| Aquatic Chronic 2 | : Hazardous to the aquatic environment — Chronic category 2. |
| Aquatic Acute 1 | : Hazardous to the aquatic environment — Acute category 1. |

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

| | |
|-----------|---|
| ADR | : European Agreement concerning the International Carriage of Dangerous Goods by Road |
| ATE | : Acute Toxicity Estimate |
| CLP | : Classification, Labeling & Packaging |
| CMR | : Carcinogenic, Mutagenic or toxic for Reproduction |
| EEC | : European Economic Community |
| IATA | : International Air Transport Association |
| IBC code | : International Bulk Chemical Code |
| IMDG | : International Maritime Dangerous Goods Code |
| LD50/LC50 | : Lethal Dose/Concentration for 50% of a population |
| MAC | : Maximum Allowable Concentration |
| MARPOL | : International Convention for the Prevention of Pollution From Ships |
| NO(A)EL | : No Observed (Adverse) Effect Level |
| OECD | : Organisation for Economic Co-operation and Development |
| PBT | : Persistent, Bioaccumulative and Toxic |
| PC | : Chemical product category |
| PT | : Product type |
| REACH | : Registration, Evaluation, Authorisation and Restriction of Chemicals |
| RID | : Regulations concerning the International Carriage of Dangerous Goods by Rail |
| STP | : Sewage Treatment Plant |
| SU | : Sector of Use |
| TWA/STEL | : Time-Weighted Average/Short Term Exposure Limit |
| UN | : United Nations |
| VOC | : Volatile Organic Compounds |
| vPvB | : Very Persistent and Very Bioaccumulative |

Number format : "," used as decimal separator.

History

Date of first issue : 30-03-2015